

JUKI



MO-6800S Series

High-speed, Overlock / Safety Stitch Machine

The advanced overlock / safety stitch machine is easier to use and promises superior cost effectiveness.



MO-6816S

MO-6800S SERIES

High-speed, Overlock / Safety Stitch Machine

SPECIFICATIONS

Model name	MO-6804S	MO-6814S	MO-6816S	MO-6843S
Stitch type	1-needle overlock	2-needle overlock	Safety stitching	3-needle safety stitching
Stitch style in the U.S.A.	504	514	516	—
Max. sewing speed	7,000sti/min*			
Stitch length	0.6 ~ 3.8 (4.5) mm			
Needle gauge (mm)	—	2.0	3.0, 5.0	3.0+2.0, 5.0+2.0
Overedging width (mm)	1.5, 4.0	2.0, 3.0, 4.0	4.0, 5.0, 6.0	3.0
Differential feed ratio	For gathering 1:2 (Max. 1:4), For stretching 1:0.7 (Max. 1:0.6)			
Needle bar stroke	24.5mm(60H:27.0mm)			
Inclination angle of the needle	20°			
Needle bar bushing	Lower bushing method			
Needle	DCx27 (excluding some subclass model)			
Max. lift of the presser foot	7mm (excluding some subclass model)			
Max. presser foot pressure	63.7N (6.5kgf)			
Stitch adjusting method	By push-button			
Differential-feed adjusting method	By lever (with micro-adjustment)			
Weight of the machine head	27kg			
Lubrication	Automatic			
Lubricating oil	JUKI Machine Oil 18 (equivalent to ISO VG18)			
Needle cooler	Provided as standard			
Needle thread heat remover	Provided as standard			
Micro-lifter	Option			

*"sti/min" stands for "Stitches per Minute."

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

Stitch type	U.S.A	Code	Type	Code	Device and attachment	Code
1-needle overlock	504	04	Standard	S	Tape attaching presser foot (for sewing sharp curves) / Tape guide	G44/Q143
2-needle overlock	514	14			Clean finish top and bottom	N075
2-needle safety stitch	516	16				
3-needle safety stitch		43				
2-needle double chain stitch		45				

MO68□□S□□□□□□/□□□□□□□□

Needle gauge (mm)	Overedging width (mm)	Feed dog	Code	Material	Application	Special machine	Code
—	1.5	2-row	0A4	Extra light- to light-weight	Light-weight materials	Rolled hemming	Standard 150
—	4.0	2-row	0E4	Light- to medium-weight	Specific to knits	Tape attaching	Standard 24H
2.0	2.0	3-row	BB6		For general fabrics	Standard	Standard 30H
2.0	3.0	3-row	BD6			Standard	Anti-marerial-slip 30P
2.0	4.0	3-row	BE6			Tape attaching	Standard 34H
3.0	4.0	2-row	DE4	Medium- to heavy-weight	Rolling-in tape	Standard 360	
3.0	4.0	3-row	DE6		Specific to knits such as sweaters	Standard	Standard 40H
5.0	5.0	3-row	FF6		Tape attaching	Standard 44H	
5.0	6.0	3-row	FH6	heavy-weight	Medium- to heavy-weight materials such as denim	Standard	Standard 50H
5.0+2.0	3.0	3-row	1D6		Standard	Standard 60H	
3.0+2.0	3.0	3-row	2D6				

JUKI ECO PRODUCTS

The MO-6800S is an eco-friendly product which complies with JUKI ECO PRODUCTS standards for protecting the environment.



The sewing machine complies with the "Juki Group Green Procurement Guidelines" on the use of hazardous substances, which is stricter than other restrictions, such as those of the RoHS Directive.

For details of JUKI ECO PRODUCTS, refer to: <https://www.juki.co.jp/en/company/eco>

*The RoHS Directive is an EU Directive limiting the use of 6 hazardous substances (lead, hexavalent chromium, mercury, cadmium, PBB and PBDE) in electrical and electronic equipment. The Juki Green Procurement Guideline is the voluntarily established criteria to eliminate not only the aforementioned six substances, but also other ones which also adversely affect the environment.



Registered Organization: JUKI CORPORATION Head Office
The Scope of the Registration: The activities of research, development, design, sales, distribution, and maintenance services of industrial sewing machines, household sewing machines and industrial robots, etc., including sales and maintenance services of data entry systems.

JUKI

JUKI CORPORATION
SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI,
TOKYO 206-8551, JAPAN
PHONE: (81) 42-357-2370
FAX: (81) 42-357-2274
<https://www.juki.co.jp/en>

- * Specifications and appearance are subject to change without prior notice for improvement.
- * Read the instruction manual before putting the machine into service to ensure safety.
- * This catalogue prints with environment-friendly soyink on recycle paper.
- * Paper from responsible sources FSC™ C001712


MO-6800S SERIES

This advanced overlock / safety stitch machine is easier to use and promises superior cost effectiveness.

The MO-6800S Series responds to various kinds of sewing materials and processes, producing delicate and beautiful soft-to-the-touch seams while further reducing operating noise as well as increasing durability. This advanced overlock / safety stitch machine is easier to use and promises superior cost-effectiveness.

The machine achieves beautifully finished seams of improved quality even when run at a high speed.

The machine is widely applicable to the sewing of light- to heavy-weight materials. Since the machine is provided with a needle thread take-up mechanism and a looper thread take-up lever, it ensures high-quality, well-tensed and soft seams with a beautiful texture which flexibly correspond to the elasticity of the materials even when run at speeds as high as 7,000 sti/min. In addition, the machine has a wider and brighter needle entry and provides improved responsiveness to the materials, thereby helping the operator use the machine more easily. The optimally-balanced design of the machine reduces both operating noise and vibration, contributing to more comfortable sewing work.



MO-6814S

The machine is provided with functions which contribute to easier operation.

The differential-feed micro-adjustment mechanism, external increasing of the differential feed ratio and the main feed dog height can all be adjustable on the front face of the sewing machine with a screwdriver. The machine is provided as standard with functions which enable easy and best-suited adjustments according to the material to be used.



Differential-feed micro-adjustment mechanism



For runstitch / MO-6816S-FF6-30H

DEVICES AND ATTACHMENTS

Model	Part No.	Description
-------	----------	-------------

Chain-off thread trimming device

T053	70000081	Pneumatic flat cutter
T054	70000082	Pneumatic side cutter (for overlock machine)

Pneumatic chain-off thread suction device

Model	Part No.	Pneumatic chain-off thread + cloth chips clutch motor	Air type auto-lifter	Clutch motor	Servo motor
MC906	70000085	●		●	
MC919	40182486	●			●
MC910	70000106	●	●	●	
MC921	40182487	●	●		●

[Reference]

Combination table of "chain-off thread suction device" and "auto-lifter" which correspond to "chain-off thread trimming device".

Chain-off thread trimming device	Chain-off thread suction device	Auto-lifter
T053 or T054	MC906	Clutch motor
	MC909	servo motor
	MC910	Air type auto-lifter clutch motor
	MC911	Air type auto-lifter servo motor

Model	Part No.	Description	Feature
-------	----------	-------------	---------

Gathering device

S206	70000089	Swing-type gathering device (interlocked with pedal / for overlock machine)(with BE6 gauge)	The attachment opens with the presser foot pedal. This facilitates material setting on the machine.
S207	70000090	Swing-type gathering device (interlocked with pedal / for safety stitch machine)(with DF6 gauge)	
S208	70000091	Swing-type gathering device (interlocked with pedal / for safety stitch machine)(with FF6 gauge)	

Guide, tape guide

H253	40159861	Cloth edge guide ruler (for overlock machine)	A swing type edge guide.
H254	40159862	Cloth edge guide ruler (for safety stitch machine)	
Q143	40159863	Tape guide	This attachment is used attached on the machine head (face plate). It is used for tapes with the width of 7mm or less.

SUBCLASS MACHINE LIST

Seams	Model No.	Materials	Number of needles	Number of threads	Needle gauge (mm)	Overredging width	Number of feed dog rows	Stitch length (mm)	Bottom differential feed ratio	Presser lifting amount (mm)	Needle system	Max sewing speed (sti/min)	Remarks
-------	-----------	-----------	-------------------	-------------------	-------------------	-------------------	-------------------------	--------------------	--------------------------------	-----------------------------	---------------	----------------------------	---------

● [1-needle overlock]

For runstitching in general fabric

	MO-6804S-0E4-30H	L~M	1	3	—	4.0	2	3.8	1:0.7~1:2	6.0	DCx27 #11	7,000	
--	------------------	-----	---	---	---	-----	---	-----	-----------	-----	-----------	-------	--

For rolled hemming (folded downward)

	MO-6804S-0A4-150	EL~L	1	3	—	1.5	2	3.8	1:0.7~1:2	6.0	DCx1 #8	7,000	
--	------------------	------	---	---	---	-----	---	-----	-----------	-----	---------	-------	--

● [2-needle overlock]

For runstitching in general fabric

	MO-6814S-BD6-30H	L~M	2	4	2.0	3.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	Anti-material-slip
	MO-6814S-BE6-40H	M~H	2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	6,500	
	MO-6814S-BB6-30P	L~M	2	4	2.0	2.0	3	3.8	1:0.7~1:2	5.0	DCx27 #11	7,000	
	MO-6814S-BE6-30P		2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.0	DCx27 #11	7,000	

For tape attaching G44: Tape attaching presser foot Q143: Tape guide

	MO-6814S-BD6-24H/G44/Q143	L~M	2	4	2.0	3.0	3	3.8	1:0.7~1:2	5.5	DCx27 #9	7,000	
	MO-6814S-BE6-24H/G44/Q143		2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #9	7,000	
	MO-6814S-BD6-34H/G44/Q143		2	4	2.0	3.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
	MO-6814S-BE6-34H/G44/Q143		2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
	MO-6814S-BE6-44H/G44/Q143	M~H	2	4	2.0	4.0	3	3.8	1:0.7~1:2	7.0	DCx27 #14	6,500	

● [Safety stitching]

For runstitching in general fabric

	MO-6816S-DE6-30H	L~M	2	5	3.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
	MO-6816S-FF6-30H		2	5	5.0	5.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
	MO-6816S-FF6-50H	M~H	2	5	5.0	5.0	3	3.8	1:0.7~1:2	7.0	DCx27 #16	6,500	
	MO-6816S-FH6-50H		2	5	5.0	6.0	3	3.8	1:0.7~1:2	7.0	DCx27 #16	6,500	
	MO-6816S-FF6-60H	H	2	5	5.0	5.0	3	4.5	1:0.9~1:1.7	7.0	DCx27 #21	6,000	
	MO-6816S-FH6-60H		2	5	5.0	6.0	3	4.5	1:0.9~1:1.7	7.0	DCx27 #21	6,000	
MO-6816S-DE4-30P	L~M	2	5	3.0	4.0	2	3.8	1:0.7~1:2	5.0	DCx27 #11	7,000	Anti-material-slip	

For rolling-in tape N075: Clean finish top and bottom

	MO-6845S-FF6-360/N075	M~H	2	4	5.0	5.0	3	3.8	1:0.7~1:2	5.0	DCx27 #14	7,000	2-needle type for double-chainstitch on pocket bags
--	-----------------------	-----	---	---	-----	-----	---	-----	-----------	-----	-----------	-------	---

● [3-needle safety stitching]

	MO-6843S-1D6-40H	M~H	3	6	5.0+2.0	3.0	3	3.8	1:0.7~1:2	6.5	DCx27 #11	7,000	
	MO-6843S-2D6-40H		3	6	3.0+2.0	3.0	3	3.8	1:0.7~1:2	6.5	DCx27 #11	7,000	

*"sti/min" stands for "Stitches per Minute."

Sewn product pictogram

